

α-650A Acrylic Glovebox



- stands above the competition with our all-welded design
- all stainless steel pipework
- Regeneration averages ~ once per year
- Automatic antechamber control
- Oxygen Analyzer / Moisture Analyzer
- Auto Vacuum
- PLC controlled with color touch panel
- EnergySave mode, Automatically reducing power consumption by up to 90% during idle periods.
- Automatic regenerable H₂O/O₂ purifier
- Attainable purity O₂<1 ppm , H₂O<1 ppm (dew point also available for moisture reading)
- Industry leading low leak rate of <0.05%Vol/h
- Circulation capacity more than 20 m³/h (50 cfm) at ΔP = 60 mbar (60 Hz)
- World-wide operation using standard power supply
- Integrated high vacuum feedthroughs
- Conform to CE

DESIGN OPTIONS

- Double Sided Access
- Left Sided Antechambers
- Vacuum Oven
- Freezer Temperature -35°C
- Through Flow Antechambers
- Laminar Flow
- Cold Well With Cover
- Regenerable Solvent Adsorber
- Dual Purification Columns
- Circular Glove Ports
- Polycarbonate Window
- Dry Vacuum Pump
- Solvent purification System
- Other Customizations

SYSTEM APPLICATIONS

- Additive (3D) Manufacturing
- Aerospace
- Automotive
- Chemistry
- Lamp Manufacturing
- Lithium Ion Battery
- Medical Device
- Nuclear
- OLED
- Pharmaceutical
- Semiconductor
- Solar
- Specialty Chemical
- Thin Film
- Many other applications

SPECIFICATIONS

Glovebox

Material: Acrylic , thickness 10 mm

Glovebox inside dimensions: 650mm(L) x 600mm(W) x 650mm(H)

Feedthrough: DN 40 ISO-KF blank and 3/8" compression bulkhead

Internal Power: Electrical feedthrough

Shelving: 3 Height adjustable 304 stainless steel

gloves: Butyl, thickness 0.4 mm

Filters: 1 Inlet/ 1 Outlet HEPA

Lighting: Fluorescent lamp, Front mounted

Power: 100-120V or 200-240 VAC 50/60 Hz 20 Amp

Leak Rate: <0.05vol%/h (ISO 10648-2)

Large Antechamber

10" (250 mm) internal diameter x 12" (300 mm) internal length

Bolt on left or right side

Internal tray: Acrylic

Automatic control: Evacuate/refill

Leak rate: < 10⁻⁵ mbar l/s

Gas purification System

Available as single purifier with solvent removal.

purity level: <1ppm O₂ and <1ppm H₂O

O₂ capacity = 23 L per purifier column

H₂O capacity = 1000 g per purifier column

Variable speed circulation blower

PLC control system 6" color touch screen

Automatic pressure control: (+/- 12 mbar)

Blower : Automated speed control: O₂ level adjusts blower speed

Circulation capacity more than 20 m³/h (50 cfm) at ΔP = 60 mbar (60 Hz)

Pressure control: Footswitch

Fully automatic regeneration sequence.

Purge valve: O₂ Level, Timer or manually controlled

Vacuum pump: 10 cfm (17 m³/h) rotary pump with oil mist eliminator

Shuts pump off for energy reduction

Oxygen Analyzer: Range 0-1000 ppm

Moisture Analyzer: Range 0-1000 ppm





Type Select

	650mm	800mm	1000mm	1200mm	1500mm	1800mm
Acrylic						
Vacuum						
Mini						
Standard						

© 2016 Nichwell LLC. rev. 08/01/2016/EA Literature made in US
Content is subject to change without notification

